



NOTES:

1. SEE WELDED WIRE FORM (WWF) FACING UNIT DETAIL FOR FACING MATERIAL AND DIMENSIONS.
2. ALL FACING UNITS SHALL BE FABRICATED FROM BLACK STEEL.
3. TOPSOIL SHALL BE LOAMY SAND OR FINER GRADATION WITH 10% - 15% ORGANIC CONTENT OR MATERIAL APPROVED BY A QUALIFIED LANDSCAPE ARCHITECT. VEGETATION TYPE SHALL BE SPECIFIED BY A QUALIFIED LANDSCAPE ARCHITECT.

WELDED WIRE FORM FACING DETAIL (PLANTABLE FACE FILL)

NOT TO SCALE

SIERRA® SLOPE RETENTION SYSTEM

MKD-WW-PE-FD-001.DWG



Tensor International Corporation | 2500 Northwinds Parkway, Suite 500 | Alpharetta, Georgia 30009
Toll Free: 1-888-828-5126 | Phone: 770-344-2090 | Fax: 770-344-2089 | www.tensorcorp.com

THIS DRAWING IS BASED UPON SPECIFIC PROPERTIES OF TENSAR PRODUCTS (GEOGRIDS, DRAINAGE COMPOSITES AND EROSION MEDIA), WHICH ARE PROPRIETARY TO TENSAR CORPORATION 1210 CITIZENS PARKWAY, MORROW, GA, 30260 AND ARE PROTECTED BY US AND INTERNATIONAL PATENTS, AND LICENSING AGREEMENTS. YOUR USE OF THE INFORMATION CONSTITUTES YOUR ACKNOWLEDGMENT OF THE PROPRIETARY NATURE OF THESE DRAWINGS AND THE TECHNOLOGY.