



NOTES:

1. SEE SIERRASCAPE® FACING UNIT DETAIL FOR FACING MATERIAL AND DIMENSIONS.
2. ALL FACING UNITS SHALL BE GALVANIZED PER ASTM A123 AFTER FABRICATION.
3. TENSAR BX1120 FACE BACKING (24" MINIMUM WIDTH) IS REQUIRED FOR AASHTO M43 No. 3 FACE STONE (1" TO 2"). BX1120 FACE BACKING IS NOT REQUIRED FOR STANDARD FACE STONE FILL (2" TO 4").
4. AASHTO M288 CLASS 3 GEOTEXTILE SEPARATION FABRIC MAY BE OMITTED IF REINFORCED FILL IS SAME AS FACING FILL.

ALTERNATIVE SIERRASCAPE® FACING DETAIL
(1"-2" STONE FACE FILL)

NOT TO SCALE

SIERRASCAPE® RETAINING WALL SYSTEM

MKE-SS-SF-FD-002.DWG



Tensar International Corporation | 2500 Northwinds Parkway, Suite 500 | Alpharetta, Georgia 30009
 Toll Free: 1-888-828-5126 | Phone: 770-344-2090 | Fax: 770 344-2089 | www.tensarcorp.com

THIS DRAWING IS BASED UPON SPECIFIC PROPERTIES OF TENSAR PRODUCTS (GEOGRIDS, DRAINAGE COMPOSITES AND EROSION MEDIA), WHICH ARE PROPRIETARY TO TENSAR CORPORATION 1210 CITIZENS PARKWAY, MORROW, GA, 30260 AND ARE PROTECTED BY US AND INTERNATIONAL PATENTS, AND LICENSING AGREEMENTS. YOUR USE OF THE INFORMATION CONSTITUTES YOUR ACKNOWLEDGMENT OF THE PROPRIETARY NATURE OF THESE DRAWINGS AND THE TECHNOLOGY.