



**GEOGRID PLACEMENT
DETAIL**

LOCKING TAIL STRUT

CUT GEOGRID TRANSVERSE BAR AT APERTURES BETWEEN WIRE PAIRS TO ALLOW CONTACT BETWEEN GEOGRID AND LOOPS (MAXIMUM OF 5 CUTS PER ROLL WIDTH OF GEOGRID)

NOTES:

1. SEE SIERRASCAPE FACING UNIT DETAIL FOR FACING MATERIALS AND DIMENSIONS.
2. TWO ROLLS OF UNIAXIAL GEOGRID SHALL BE PLACED ON EACH SIERRASCAPE FACING UNIT WITH TWO GEOGRID RIBS BETWEEN EACH PAIR OF WIRE CONNECTION LOOPS.
3. DURING INSTALLATION BUTT VERTICAL WIRE OF ADJACENT FACING UNITS TO PROVIDE 2.4" OVERLAP OF HORIZONTAL WIRES.

TYPICAL SIERRASCAPE® GEOGRID COVERAGE

NOT TO SCALE

SIERRASCAPE® RETAINING WALL SYSTEM

MKE-SS-GE-FD-001.DWG



Tensor International Corporation | 2500 Northwinds Parkway, Suite 500 | Alpharetta, Georgia 30009
Toll Free: 1-888-828-5126 | Phone: 770-344-2090 | Fax: 770 344-2089 | www.tensorcorp.com

THIS DRAWING IS BASED UPON SPECIFIC PROPERTIES OF TENSAR PRODUCTS (GEOGRIDS, DRAINAGE COMPOSITES AND EROSION MEDIA), WHICH ARE PROPRIETARY TO TENSAR CORPORATION 1210 CITIZENS PARKWAY, MORROW, GA, 30260 AND ARE PROTECTED BY US AND INTERNATIONAL PATENTS, AND LICENSING AGREEMENTS. YOUR USE OF THE INFORMATION CONSTITUTES YOUR ACKNOWLEDGMENT OF THE PROPRIETARY NATURE OF THESE DRAWINGS AND THE TECHNOLOGY.