



NOTES:

1. SEE WELDED WIRE FORM (WWF) FACING UNIT DETAIL FOR FACING MATERIALS AND DIMENSIONS.
2. INSTALL ADJACENT WWF FACING UNITS TO PROVIDE 4" OVERLAP OF HORIZONTAL WIRES.
3. GEOGRID GAPS DENOTED BY 'X' SHALL BE CENTERED OVER THE CENTERLINE OF A GEOGRID ROLL WIDTH IN THE LAYER BELOW.
4. WHEN WALL LAYOUT INCLUDES A CORNER/TURN, FULL GEOGRID COVERAGE IS REQUIRED. REFER TO ELEVATION VIEW FOR LIMITS OF FULL GEOGRID COVERAGE.

PERCENT COVERAGE	X
100	0
74	18"
59	36"

TYPICAL WWF GEOGRID COVERAGE

NOT TO SCALE

SIERRA® SLOPE RETENTION SYSTEM

MKD-WW-GE-FD-001.DWG



Tensor International Corporation | 2500 Northwinds Parkway, Suite 500 | Alpharetta, Georgia 30009
Toll Free: 1-888-828-5126 | Phone: 770-344-2090 | Fax: 770 344-2089 | www.tensorcorp.com

THIS DRAWING IS BASED UPON SPECIFIC PROPERTIES OF TENSAR PRODUCTS (GEOGRIDS, DRAINAGE COMPOSITES AND EROSION MEDIA), WHICH ARE PROPRIETARY TO TENSAR CORPORATION 1210 CITIZENS PARKWAY, MORROW, GA, 30260 AND ARE PROTECTED BY US AND INTERNATIONAL PATENTS, AND LICENSING AGREEMENTS. YOUR USE OF THE INFORMATION CONSTITUTES YOUR ACKNOWLEDGMENT OF THE PROPRIETARY NATURE OF THESE DRAWINGS AND THE TECHNOLOGY.