



# Roadway Drainage System

## Specification Sheet – ROADRAIN 5 (RD-5)

ROADRAIN 5 is a Synthetic Subsurface Drainage Layer (SSDL) comprised of a tri-planar structure with thermally bonded 6 oz. nonwoven geotextile filters on both sides. This product quickly removes subsurface water from pavement base and sub-base layers, while providing a void-maintaining system to work as a capillary break. ROADRAIN 5 also works as a separation layer. ROADRAIN 5 has properties conforming to the values and test methods listed below:

Property	Test Methods	Units	Value	Qualifier
<b>Tri-Planar Core<sup>1</sup></b>				
Density	ASTM D 792	g/cm <sup>3</sup>	0.94 – 0.96	Range
Carbon Black	ASTM D 4218	%	2-3	Range
Rib Spacing (top & bottom)	Calipered	in. (mm)	0.4 (10)	Typical
Central Rib Spacing	Calipered	in. (mm)	0.5 (12.5)	Typical
Unsupported Aperture Area	Calipered	in. <sup>2</sup> (mm <sup>2</sup> )	0.3 (195)	MAX
Thickness	ASTM D 5199	mil (mm)	280 (7.1)	±10%
<b>Nonwoven Geotextile<sup>1</sup></b>				
Strength	AASHTO M 288		Exceeds Class 2	
U.V. Resistance (500 hrs)	ASTM D 4355	%	70	MARV
AOS	ASTM D 4751	US Std Sieve (mm)	70 (0.212)	MaxARV
Permittivity	ASTM D 4491	sec <sup>-1</sup>	1.4	MARV
Water Flow Rate	ASTM D 4491	gpm/ft <sup>2</sup> (l/min/m <sup>2</sup> )	110 (4481)	MARV
<b>SSDL Performance</b>				
Capillary Barrier	ASTM 5918		Effective	Notes <sup>2</sup>
Coefficient of Permeability	ASTM D 4716	ft/day	56,700	Notes <sup>3</sup>
<b>Dimensions &amp; Flow Orientation</b>				
Roll Size		12.75 ft x 200 ft (3.89 m x 61 m)		
Direction of Primary Flow		Across the roll width @ approximately 45°		

Qualifiers: MARV = Minimum Average Roll Value (MARV), MAV = Minimum Average Value, MAX = Maximum Value, MaxARV = Maximum average roll value.

**NOTES:**

1. Geotextile and core properties listed are prior to lamination.
2. As tested by the USACE Cold Regions Research and Engineering Laboratory (CRREL).
3. Coefficient of permeability is calculated with the measured SSDL transmissivity and the nominal core thickness. SSDL transmissivity is tested along the primary flow direction with the boundary conditions as follows: steel plate/Ottawa sand/SSDL/Ottawa sand/steel plate, one hour seating period @ 5,000 psf and gradient 2%.



Tensor International Corporation  
 2500 Northwinds Parkway  
 Suite 500  
 Alpharetta, GA 30009  
 800-TENSAR-1  
 tensorcorp.com

©2012, Tensor International Corporation. Certain products and/or applications described or illustrated herein are protected under one or more U.S. patents. Other U.S. patents are pending, and certain foreign patents and patent applications may also exist. Trademark rights also apply as indicated herein. Final determination of the suitability of any information or material for the use contemplated, and its manner of use, is the sole responsibility of the user. Printed in the U.S.A.