

GlasPave® Waterproofing Paving Mat

Specification Sheet - GlasPave® 25/50 Waterproofing Paving Mat

Specifications for Use in Asphalt Overlays					
Property	Test Method	GP25		GP50	
		Metric	Imperial	Metric	Imperial
Tensile Strength (Ultimate) (MD X XD)	ASTM D5035 EN-ISO 10319	25 x 25 kN/m	142 x 142 lbs/in.	50 x 50 kN/m	285 x 285 lbs/in.
Tensile Elongation	ASTM D5035 EN-ISO 10319	< 5%	< 5%	< 5%	< 5%
Young's Modulus E		73,000 MPa	10.6 x 10 ⁶ psi	73,000 MPa	10.6 x 10 ⁶ psi
Mass/Unit Area	ASTM D5261 ISO 9864	136 g/m²	4.0 oz/yd²	237 g/m²	7.0 oz/yd²
Asphalt Retention	ASTM D6140 EN 15381 Annex C	0.47 l/m²	0.10 gal/yd²	0.47 l/m²	0.10 gal/yd²
Melting Point	ASTM D276 EN-ISO 3146	> 232°C	> 450°F	> 232°C	> 450°F
Roll Size		1.27 x 228.6 m 1.91 x 228.6 m 3.81 x 109.7 m	50 in x 250 yds 75 in x 250 yds 150 in x 120 yds	1.91 x 109.7 m 3.81 x 65.8 m	75 in x 120 yds 150 in x 72 yds
Roll Area		290 m ² 436 m ² 418 m ²	347 yd² 521 yd² 500 yd²	209.0 m ² 250. 8 m ²	250 yd² 300 yd²

The values and tolerances given are obtained in our laboratories and in accredited testing institutions. All imperial values are approximate. The information given in this data sheet is to the best of our knowledge true and correct. However new research and practical experience can make revisions necessary. We reserve the right to make changes at any time. Statements concerning possible use of our product are not intended as recommendations for their use in the infringement of any patent. No patent warranty of any kind, expressed or implied, is made or intended.



Tensar International Corporation 2500 Northwinds Parkway Suite 500 Alpharetta, GA 30009 800-TENSAR-1 tensarcorp.com GlasPave® is distributed in the United States of America, Canada and certain other countries by Tensar International Corporation (Tensar). Inasmuch as Saint-Gobain ADFORS and Tensar have no control over installation design, installation workmanship, accessory materials, or conditions of application, Saint-Gobain ADFORS and Tensar do not warrant the performance or results of any installation or use of GlasPave®. This warranty disclaimer includes all implied warranties, statutory or otherwise, including the warranty of merchantability and of fitness for a particular number.

©2016, Tensar International Corporation

